



Revision: August 1, 2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Penetrating oil

Lubricant

- · 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:
 Synco Chemical Corporation
 24 DaVinci Dr., P.O. Box 405
 Bohemia, NY 11716

Telephone: 631-567-5300 Email: info@super-lube.com

· 1.4 Emergency telephone number:

CHEMTREC

1-800-424-9300 (US/Canada) +01 703-527-3887 (International)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EU) No 2015/830



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· Additional information: 0 percent of the mixture consists of component(s) of unknown toxicity

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light

heptane

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 3)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 2)

· Additional information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

- Hazard description:
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2	Distillates (petroleum), hydrotreated light Asp. Tox. 1, H304	50-100%
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide Press. Gas L, H280	2,5-10%

[•] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 3)

After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

· 4.2 Most important symptoms and effects, both acute and delayed

Frostbite

Irritating to eyes and skin.

Coughing

Breathing difficulty

Dizziness

Nausea

· Hazards

Danger of pulmonary oedema.

Danger of pneumonia.

Danger of impaired breathing.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

Treat frost-bitten areas appropriately.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Danger of receptacles bursting because of high vapour pressure when heated.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Cool endangered receptacles with water fog or haze.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 5)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 4)

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

Information about fire - and explosion protection:

Protect against electrostatic charges.

Emergency cooling must be available in case of nearby fire.

Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from oxidising agents.

· Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

·7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 6)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 5)

· 8.1 Control parameters

0:1 Control para				
· Ingredients with limit values that require monitoring at the workplace:				
64742-47-8 Distillates (petroleum), hydrotreated light				
MAK (Germany)	Long-term value: 140 mg/m³, 20 ppm vgl.Abschn.Xc			
142-82-5 heptane				
IOELV (EU)	Long-term value: 2085 mg/m³, 500 ppm			
PEL (USA)	Long-term value: 2000 mg/m³, 500 ppm			
REL (USA)	Long-term value: 350 mg/m³, 85 ppm Ceiling limit: 1800* mg/m³, 440* ppm *15-min			
TLV (USA)	Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm			
MAK (Germany)	Long-term value: 2100 mg/m³, 500 ppm vgl.Abschn.XII			
124-38-9 carbon dioxide				
IOELV (EU)	Long-term value: 9000 mg/m³, 5000 ppm			
PEL (USA)	Long-term value: 9000 mg/m³, 5000 ppm			
REL (USA)	Short-term value: 54,000 mg/m³, 30,000 ppm Long-term value: 9000 mg/m³, 5000 ppm			
TLV (USA)	Short-term value: 54,000 mg/m³, 30,000 ppm Long-term value: 9000 mg/m³, 5000 ppm			
AGW (Germany)	Long-term value: 9100 mg/m³, 5000 ppm 2(II);DFG, EU			

- · **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

(Contd. on page 7)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 6)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information. No further relevant information available.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Colour:
Odour:
Golvent-like
Odour threshold:
PH-value:

Aerosol
Translucent
Solvent-like
Not determined.
Not determined.

Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Not applicable, as aerosol.
Not applicable, as aerosol.

Extremely flammable aerosol.

Extremely flammable aerosol.

· Auto/Self-ignition temperature: 210 °C

· **Decomposition temperature:** Not determined.

(Contd. on page 8)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 7)

· **Self-igniting:** Product is not self-igniting.

Danger of explosion: Not determined.

· Explosion limits:

Lower: 1,1 Vol % **Upper:** 7 Vol %

Vapour pressure: Not determined.
Density: Not determined.
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC (California) < 25%

Exempt VOCs are excluded from this value

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapour pressure when heated.

· 10.3 Possibility of hazardous reactions

Develops readily flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Extremely flammable aerosol.

Used empty containers may contain product gases which form explosive mixtures with air.

Reacts with strong oxidising agents.

Toxic fumes may be released if heated above the decomposition point.

· 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Keep away from heat and direct sunlight.

Store away from oxidising agents.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

(Contd. on page 9)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 8)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:			
64742-47-8 Distillates (petroleum), hydrotreated light			
Oral	LD50	> 5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
142-82-5 heptane			
Oral	LD50	> 5000 mg/kg (rat) (Estimate)	
Inhalative	LC50/4h	103 mg/l (rat)	

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitisation: No sensitising effects known.
- Additional toxicological information:

Irritant

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· Acute effects (acute toxicity, irritation and corrosivity):

Vapours have narcotic effect.

Irritating to skin.

May be fatal if swallowed and enters airways.

· Repeated dose toxicity: May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

(Contd. on page 10)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 9)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Contact waste processors for recycling information.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · DOT, ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).

· **DOT** Aerosols, flammable

· ADR 1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS

· IMDG AEROSOLS (HEPTANES), MARINE POLLUTANT

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· DOT



· Class 2.1 · Label 2.1

· ADR





· Class 2 5F Gases.

(Contd. on page 11)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 10) · Label 2.1 ·IMDG 2.1 · Class · Label 2.1 · IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · DOT, ADR, IMDG, IATA Not Regulated · 14.5 Environmental hazards: Product contains environmentally hazardous substances: heptane · Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Gases. Danger code (Kemler): · EMS Number: F-D,S-U · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category · Tunnel restriction code · IMDG · Limited quantities (LQ) 1L **Excepted quantities (EQ)** Code: E0 Not permitted as Excepted Quantity · UN "Model Regulation": UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

(Contd. on page 12)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 11)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Carcinogenic Categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas L: Gases under pressure: Liquefied gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

(Contd. on page 13)

Revision: August 1, 2019

Trade name: Super Lube® Syncopen® Synthetic Penetrant Aerosol

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com